

CROSSOVER

In a class by itself!



*The world's first small
laundry machines
engineered to
commercial standards.*

*Perfect for all
on-premise laundry
operations.*

 **Wascomat**

CROSSOVER

Crossover is a revolutionary product engineered *exclusively* for commercial use. Washers are designed to last 15,000+ cycles—more than double the life of appliances top load and front load washers made for home use.

- ✓ **Designed for three liquid chemical connections with clean pump signals.**
- ✓ **No oversudsing! Crossover will complete the cycle.**
- ✓ **CrossBalance technology keeps loads balanced.**
- ✓ **Built tough with top quality SKF bearings, triple seals, solid steel counterweights, and 8-point suspension system.**
- ✓ **All Crossover machines are soft-mount with pump drain for easy installation.**

Replace your appliance-type front loaders and top loaders with a true commercial laundry system from Wascomat.

When Laundry Means Business!



NON-METERED STACKING WASHER AND DRYER—(GAS HEAT DRYER)
Model No. WDSGMM

NON-METERED STACKING WASHER AND DRYER—ELECTRIC Model No. WDSENM

FEATURES AND BENEFITS

WASHER

- ✓ 22+ lb capacity
- ✓ 15,000+ cycles durability
- ✓ 4 professional wash programs + 2 cycle options
- ✓ Top quality SKF bearings in heavy duty assembly
- ✓ 3 seals with 5 lips protect bearings
- ✓ Professional grade 8-point suspension
- ✓ Pump-drain standard
- ✓ Solid steel counterweights—no concrete

DRYER

- ✓ 22+ lb capacity
- ✓ 7.5 cu ft drum
- ✓ Durable stainless steel fixed lint screen

- ✓ Axial airflow
- ✓ Commercial grade components
- ✓ Extra large door opening
- ✓ Roller supported tumbler
- ✓ Heavy steel construction
- ✓ Tapered ribs bring load forward improving dryer performance.

BEST CUSTOMER EXPERIENCE

WASHER

- ✓ Superior oversuds and unbalance tolerance
- ✓ Extra large door opening
- ✓ Heavy-duty door hinge
- ✓ 4 wash programs + 2 options
- ✓ High speed 300G max extraction

DRYER

- ✓ Faster and more efficient drying
- ✓ Easy loading and unloading with the extra large door opening
- ✓ Large capacity tumbler can handle oversized loads
- ✓ Commercial grade components for maximum dependability and longer life

MARKET READY DESIGN

- ✓ Space-saving 27" wide to minimize floor space
- ✓ Quiet operation
- ✓ Liquid chemicals are fully diluted with water

CEE TIER 3
COMPLIANT



CROSSOVER OPL WASHER Model No. WHWF09810NM



CROSSOVER DRYER—GAS Model No. DAWF0GNM

CROSSOVER DRYER—ELECTRIC Model No. DAWF0ENM

CROSSOVER WASHER SPECIFICATIONS

Model No.	Non-Metered/Card Ready WHWF09810NM
Motor	Variable-speed, reversible, thermoprotected, high-efficiency, controlled induction
Electrical Rating	120 V/60 Hz / 1-phase
Breaker Requirements	15A
Cylinder Volume	3.5 cu ft (98 liters)
Cylinder Diameter	21 5/8 in (550 mm)
Cylinder Depth	18 1/4 in (464 mm)
Wash Capacity	22 lbs (10 kg)
Door Opening	15 in (380 mm)
Wash Speed	45 RPM
Maximum RPM*	1,000 RPM
Maximum G-force*	300 G
Inlet Hose	2 3/8 in (hoses included)
Water Pressure	10-90 psi (70-600 kPa)
Drain Hose	1 in (25.4 mm)
Crated Weight	314 lbs (142.7 kg)
Uncrated Weight	299 lbs (136 kg)
Overall Dimensions	W D H: 27 x 33 3/4 x 39 3/4 in w/o meter box W D H: 27 x 33 3/4 x 43 1/2 in w/meter box (W D H: 686 x 857 x 1010 mm w/o meter box) (W D H: 686 x 857 x 1106 mm w/meter box)

CROSSOVER DRYER SPECIFICATIONS

Model No.	Non-Metered/Card Ready Gas DAWF0GNM
Model No.	Non-Metered/Card Ready Electric DAWF0ENM
Motor	1/3 HP
Electrical Rating (Gas Model)	120V/60Hz/1-phase
Electrical Rating (Electric Model)	208-240V/60Hz/1-phase
Breaker/Fuse Requirements (Gas Heat)	15A
Breaker/Fuse Requirements (Electric Heat)	30A
Cylinder Volume	7 1/2 cu ft (212 liters)
Cylinder Diameter	25 3/4 in (654 mm)
Cylinder Depth	24 in (609 mm)
Capacity (Dry Weight)	22 lbs (10 kg)

Door Opening	17 1/4 in (438 mm)
Airflow	220 cfm (340 m3/h)
Gas Heating	26,000 Btu/hr (6,550 kcal/hr)
Gas Connection	3/8 in MNPT
Tumbling Speed	50 RPM
Exhaust Connection	4 in
Approximate Net Weight	151 lbs (68.6 kg)
Approximate Shipping Weight	171 lbs (77.7 kg)
Overall Dimensions	W D H: 27 1/8 x 31 3/4 x 44 in W D H: 685 x 759 x 1118 mm

CROSSOVER STACK WASHER/DRYER SPECIFICATIONS

Model No.	DAWF52GM - Gas
Model No.	DAWF52EM - Electric
Motor	1/3 HP
Electrical Rating (Gas Model)	120VAC/60Hz/2W/1-phase
Electrical Rating (Electric Model)	208-240V/ 60Hz/1-phase
Breaker/Fuse Requirements (Gas)	15A
Breaker/Fuse Requirements (Electric)	30A
Cylinder Volume	7.5 cu ft/ 212.4 liters
Cylinder Diameter	25 3/4 in
Cylinder Depth	24 in
Capacity (Dry Weight)	10Kg/22lbs
Door Opening	17 1/4 in (438 mm)
Airflow (Gas & Electric)	220 cfm
Electric Heating (240VAC)	5.4 kW
Gas Heating	26,000 Btu/hr (6,550 kcal/hr)
Gas Connection	3/8 in MNPT
Tumbling Speed	50 rpm
Exhaust Connection	4in Dia.
Overall Dimensions	W D H: 27 1/8 x 31 3/4 x 77 1/2 in
Overall Dimensions	W D H: 686 x 807 x 1968 mm
Approximate Net Weight	151 lbs

Laundrylux offers a complete line of Electrolux professional and Wascomat commercial laundry equipment.

*NOTE: the correct measurement of extraction efficiency is G-force, not RPM. A higher RPM does not mean greater extraction, which depends on cylinder diameter.

Laundrylux®

866.580.1010 ✓ laundrylux.com/crossover

Email inquiries to crossover@laundrylux.com

Technical questions? Call 516.371.0700