



Thinking of you
Electrolux

Electrolux Professional Line 5000

Electrolux Dryers Stack and Single Pocket Coin/Card

Use up to 40% less gas and dry 12% faster

Built to last, Electrolux dryers are precision-engineered for efficiency, ease of use, and superior drying results. You will use less gas and dry faster than with competing brands. Pair Electrolux dryers with Electrolux high G-force washers, and you create an even stronger competitive edge: increased load capacities, faster drying, less wear and tear on garments, lower energy consumption, and time savings. Your customers will love the fast drying and user-friendly controls. You'll appreciate the "green" engineering, cost savings, easy operation, and years of low maintenance.

Features and Benefits:

- Dries 12% faster, saving 25% in gas due to axial airflow, tight construction, and reversing cylinders
- Save up to an additional 15% of energy consumption with EcoPower. Less wear-and-tear on garments and prevents over-drying
- Best lint screen in the industry - easiest to clean, ergonomically designed
- Large door opening for easy loading and unloading
- Excellent water evaporation efficiency per kWh
- Reversing drums (standard) reduces energy consumption, prevents tangling – and laundry dries more quickly
- 120 volt, single-phase for easy installation

Compass Pro microprocessor offers:

- Large display and one control knob for easy program selection
- More than 20 languages available - Displays two languages, simultaneously
- Real-time clock for time of day pricing, happy hour pricing and promotions
- Detailed user statistics and programmability
- USB connection in front, easily accessible

Main Options

- Stainless steel front and drum
- Frequency controlled motor

Accessories

- Fresh air intake
- Exhaust on top



Available in 35x35 and 50x50 stacks, 35, 67 and 83 lb. capacities. Vertical blue wave front panel standard. Stainless available. Choice of card ready or drop coin payment.

Electrolux energy savings have been measured extensively. Results may vary depending on installation and other conditions.



Designed by experts. Inspired by you.

For more information, please visit www.laundrylux.com

Model	T5300S		T5420S		T5290		T5550		T5675		T4900		T41200	
Capacity (lb/kg)	2 x 35	2 x 15.9	2 x 50	2 x 22.7	35	15.9	67	30.4	83	37.7	100	45.4	135	61.2
Width (in/mm)	31 1/8	790	34 1/4	870	27 15/16	710	37 13/16	960	37 13/16	960	50 13/16	1290	50 13/16	1290
Depth (in/mm)	43 7/8	1115	52 5/8	1336	45 1/2	1155	51 3/4	1315	59 7/16	1510	51	1295	58 7/16	1485
Depth with door open (in/mm)	72 7/16	1840	85 5/8	2175	68 5/16	1735	83 11/16	2125	91 5/16	2320	94 1/2	2400	101 15/16	2590
Height Overall (in/mm)	76 3/8	1940	81 7/8	2078	65 15/16	1675	73 7/16	1855	73 7/16	1855	97 1/16	2465	97 1/16	2465
Height without heating unit (in/mm)	n/a		n/a		n/a		n/a		n/a		77 3/8		77 3/8	
Door opening diameter (in/mm)	22 7/8	580	27	686	22 13/16	580	31 7/8	810	31 7/8	810	37	940	37	940
Cylinder volume (ft3/l)	10.6	300	14.6	414	10.2	290	19.4	550	23.8	675	31.8	900	42.4	1200
Crated Weight (lb/kg)	695	315	865	392	518	235	717	325	827	375	1100	500	1166	530
Utility Connections			(2) 8" or (1) 10"											
Exhaust duct diameter (in/mm)	8	200	(2) 203mm or (1) 254mm		8	200	10	250	10	250	12	315	12	315
Gas connection	1/2 NPT		3/4 MNPT		1/2 NPT		1/2 NPT		3/4 NPT		1 NPT		1 NPT	
Steam connection, inlet & condensate	n/a		n/a		1 NPT		1 NPT		1 NPT		1 NPT		1 NPT	
Energy Data														
Gas (Btu/hr)	2 x 71,700		2 x 94,000		71,700		112,700		143,400		219,000		280,000	
Airflow (ft3/min / m3/hr) (gas heat)	2 x 354	2 x 600	2 x 600	2 x 1020	360 / 610		550 / 940		670 / 1140		1354 / 2300		1765 / 3000	
3000Electric (kW) @ 208-240V/3Ø	2 x 18	n/a	18	30	13.5 or 18		24 or 32		24 or 32		32		72	
Airflow (ft3/min / m3/hr) (elec. heat)	2 x 354	2 x 600	n/a		325 / 550		550 / 940		670 / 1140		1354 / 2300		1765 / 3000	
Steam (lb/hr / kg/hr) (approximate)	n/a		n/a		80 / 36		118 / 54		150 / 68		315 / 143		315 / 143	
Airflow (ft3/min / m3/hr) (steam heat)	n/a		n/a		405 / 690		635 / 1080		810 / 1380		1354 / 2300		1765 / 3000	
Electrical Requirements														
Current, gas or steam, 120 V/60Hz (full load/circuit breaker)	2 x 9A / 2 x 15A		2 x 12A / 2 x 15A		7.5A (15A)		12A (20A)		12A (20A)		n/a		n/a	
Current, gas or steam, 208-240 V/60Hz/1Ø (full load/circuit breaker)	2 x 4.5A / 2 x 15A		5.50A / 15A		3.5A (15A)		8.5A (15A)		8.5A (15A)		n/a		n/a	
Current, gas or steam, 208-240 V/60Hz/3Ø (full load/circuit breaker)	n/a		n/a		3.75A (15A)		10A (15A)		10A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	2 x 50 / 2 x 65		n/a		14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)		75 / 100 @ 480 Volts		90 / 125 @ 480 VoltsAlternate	
Alternate Voltages														
Alternate voltages available. Contact Laundrylux Sales Department for information.														
Supply Pressures														
Natural Gas (inches H2O/mbar)	6-10 / 15-25		6-12 / 15-30		3.5-10.5 / 9-26		3.5-10.5 / 9-26		3.5-10.5 / 9-26		6-10 / 15 - 25		6-10 / 15 - 25	
Propane (inches H2O/mbar)	10-13 / 25-30		11-13 / 28-33		8-13 / 20-32		8-13 / 20-32		8-13 / 20-32		10-13 / 25-30		10-13 / 25-30	
Steam (psi/bar) (max)	n/a		145 / 10		145 / 10		145 / 10		145 / 10		145 / 10		145 / 10	
Exhaust back pressure (inches H2O/mbar) (max)	1.57	3.9	0.6	1.5	2.2	5.5	2.6	6.48	3	7.5	0.37	1	0.37	1
<p><i>Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.</i></p>														




Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



Dry faster using 25% less gas thanks to tight construction and axial airflow



Longer machine life with support rollers and advanced blower wheel



Up to 15% less energy with EcoPower



Reversing Cylinders for time and energy savings

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux

800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

