Huebsch is the answer.



Commercial Front Load Washer Specifications

Convenience and Efficiency

What sets Huebsch front load washers apart from the competition?



(A) Low water use.

Huebsch front load washers average just 10.4 gallons of water per cycle. Best of all, the washer is so efficient it's earned an ENERGY STAR® rating.



Model

Motor* - HP



(High spin speed.

With a final spin of 1,000 RPM, Huebsch front load washers exert 300 G-Force on loads to remove more water, reduce drying times and lower utility consumption. This is the same G-Force many top-of-the-line large capacity washer-extractors exert in commercial laundries.



(A) Large, rugged doors.

Our washer's large 188.6 sq. in. door opening speeds the often awkward and time-consuming tasks of loading and unloading. In addition, the solid door



features a durable piano style, steel hinge.



riangle Stainless steel inside and out.

For extra durability, Huebsch front load washers feature a stainless steel finish option. The stainless steel strength carries over to the inner and outer tubs that will stay looking good for years. A fact backed up with a lifetime warranty on the tubs.



(H) Convenience.

A frontmount supply dispenser automatically adds detergent, bleach and softener.



Model	TIFININ (Walaxy)
Speeds	1000, 650, 500
Cycles	Heavy, Normal, Perm Press and Delicate
Water Temperatures	Hot, Warm, Cold
Stainless Steel Washtub	2.84 cu. ft.
Water Pressure - psi (bar)	Fill 20-120 (1.4/8.3)
Wash/Tumble - RPM	41, 50
Distribution/Pump - RPM	90
Spin Speeds - RPM	1000, 650, 500
Activation	Coin/Card Operated
Dispenser	Detergent, Liquid Bleach, Liquid Softener

Variable Speed Induction, 1

HFNS (E-Mech) HFNB (MDC)

HENN (Galavy)

Top Finish	Stainless Steel, Porcelain
Color	Stainless Steel, White
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height** - in (mm)	43" (1092)
Work Surface Height** - in (mm)	43" (1092) Front Control / 36" (910) Rear Control
Weight - Ib (kg)	250 (113)

^{*} Motor: 1 HP reversing, permanently lubricated with a built-in electronic protector.

cl II us

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A.

Agency Approvals

©Copyright 2013 Alliance Laundry Systems LLC

Unmatched Durability

What sets Huebsch apart from other brands in terms of reliability?



(A) Not just standing behind our equipment, but standing beside you and your business.



Our made-in-America product comes with an industryleading bond. The entire machine receives Huebsch's standard three-year warranty. In addition, Huebsch has more service representatives in the field than most brands have in their whole organization. Huebsch support is further bolstered by an online component and a help line that takes 10,000 calls per year.

^{**} Heights may vary slightly depending on leveling adjustments.

^{*}Parts only, labor not included. See Huebsch Warranty Bond for specifics.