

TD Dryers – Stack & Single Pocket

Wascomat Commercial TD Dryer models are precision-engineered for efficiency, ease of use, and superior drying results. Our single pocket dryers now have easy to use Compass Pro control. Wascomat dryers are your best choice for reliability, durability, and customer satisfaction. Perfect for coin/card laundries, customers love the fast drying and user-friendly controls.



30x30, 45x45, 35, 67 and 83 lb. capacities.
Coin and card-ready.

Features and Benefits:

- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the fastest drying with lowest energy consumption
- Extra large doors make loading and unloading easy
- Convenient access to parts
- Easy to clean lint screen – best in the industry
- Quiet operation. Our dryers are designed to keep noise level below 70 dB (A)
- Reverse drum operation (option) minimizes tangling and wrinkling, and improves dryer efficiency
- Sturdy drum suspension with double-sealed bearings and belt drive

Single Pocket Dryer features:

- **Axial Airflow** and tight construction for extremely low energy consumption
 - Dries 12% faster, saving 25% in gas
- **Compass Pro program control**
 - Large and clear display with control knob for easy program selection
 - Easy to program, easy access to USB
 - Language selection - Displays two languages at one time
 - Service program for adjustment of parameters
- **Selecta II**
 - 4 temperature settings
 - Displays remaining drying time
 - Coin, token, debit card compatible
 - Complete diagnostics & service model
- Top Exhaust Kit (*optional*)

Wascomat dryers offer reliability, durability and significant energy savings for self-service laundries.

TD DRYER CONTROLS

Compass Pro

- Compass Pro available on single pocket Wascomat dryers.



Selecta II Coin/Card

- Selecta II on 30x30 and 45x45 Stack dryers.



Wascomat TD Dryers - Stack & Single Pocket	TD 30x30		TD 45x45		TD35		TD67		TD83	
Capacity (lb/kg)	2 x 30	2 x 13.6	2 x 45	2 x 20.4	35	15.9	67	30.4	83	37.6
Width (in/mm)	31 1/8	790	34 1/4	870	27 15/16	710	37 13/16	960	37 13/16	960
Depth (in/mm)	43 11/16	1110	52 5/8	1336	45 1/2	1155	51 3/4	1315	59 7/16	1510
Depth with door open (in/mm)	72 7/16	1840	85 5/8	2175	68 5/16	1735	83 11/16	2125	91 5/16	2320
Height Overall (in/mm)	76 3/8	1940	81 7/8	2078	65 15/16	1675	73 7/16	1855	73 7/16	1855
Height without heating unit (in/mm)	n/a		n/a		n/a		n/a		n/a	
Door opening diameter (in/mm)	22 7/8	580	27	686	22 13/16	580	31 7/8	810	31 7/8	810
Cylinder volume (ft ³ /l)	10.6	300	14.6	414	10.2	290	19.4	550	23.8	675
Crated Weight (lb/kg)	693	315	865	392	518	235	717	325	827	375
Utility Connections			(2)8" or (1)10"							
Exhaust duct diameter (in/mm)	8	200	(2)203mm or (1) 254mm		8	200	10	250	10	250
Gas connection	1/2 NPT		3/4 MNPT		1/2 NPT		1/2 NPT		1/2 NPT	
Energy Data										
Gas (Btu/hr)	2 x 71,700		2 x 94,000		71,700		112,700		143,400	
Airflow (ft ³ /min / m ³ /hr) (gas heat)	2 x 354	2 x 600	2 x 600	2 x 1020	360 / 610		550 / 940		670 / 1140	
3000Electric (kW) @ 208-240V/3Ø	2 x 18	n/a	18	30	13.5 or 18		24 or 32		24 or 32	
Airflow (ft ³ /min / m ³ /hr) (elec. heat)	2 x 354	2 x 600	n/a		325 / 550		550 / 940		670 / 1140	
Steam (lb/hr / kg/hr) (approximate)	n/a		n/a		80 / 36		118 / 54		150 / 68	
Airflow (ft ³ /min / m ³ /hr) (steam heat)	n/a		n/a		405 / 690		635 / 1080		810 / 1380	
Electrical Requirements										
Current, gas or steam, 120 V/60Hz(full load/circuit breaker)	2x9A / 2x15A		2 x 12A / 2 x 15A		7.5A (15A)		12A (20A)		12A (20A)	
Current, gas or steam, 208-240 V/60Hz/1Ø(full load/circuit breaker)	2x4.5A / 2x15A		5.50A / 15A		3.5A (15A)		8.5A (15A)		8.5A (15A)	
Current, gas or steam, 208-240 V/60Hz/3Ø(full load/circuit breaker)	n/a		n/a		3.75A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	2x50 / 2x65		n/a		14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)	
Alternate Voltages										
Alternate voltages available. Contact Laundrylux Sales Department for information.										
Supply Pressures										
Natural Gas (inches H2O/mbar)	6-10 / 15-25		6-12 / 15-30		3.5-10.5 / 9-26		3.5-10.5 / 9-26		3.5-10.5 / 9-26	
Propane (inches H2O/mbar)	10-13 / 25-30		11-13 / 28-33		8-13 / 20-32		8-13 / 20-32		8-13 / 20-32	
Exhaust back pressure (inches H2O/mbar) (max)	1.57	3.9	0.6	1.5	2.2	5.5	2.6	6.48	3	7.5

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.



Laundrylux
800.645.2205 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com
Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com
Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010



TD45x45 is CSA certified. Other TD dryers are ETL certified.